MULTILED LT Max

MULTILED LT MAX	
Luminous Flux	White, 24.000 lumen
Power consumption	240W
Supply Voltage	24 Vdc
Bundled PS	Standard desktop PS 24 V 240 W
Connector	XLR 4 Pin
Heat Dissipation	Heat sink with temperature controlled fan
Environmental temp. (operation)	-25°C to +40°C
Temp. (Storage)	-25°C to +80°C
Overheat Protection	Thermo switch turns off power at 72°C and turns on when temperature falls < 60°C
IP class	IP 20
Mounting Options	1/4" thread
Standard Lenses	12° FWHM
Alternative lenses	12° Spot, medium, wide, extra wide, 120°
Dimensions	146 x 106 x 88 mm
Weight	1.365 g
LED	24 high power LED

ALTERNATIVE LED TYPES (STANDARD: COLD WHITE 24.000 LM)		
COLOR	**PEAK WAVELENGHT NM**	**RADIANT FLUX MW**
Blue	440 - 460	80.000
Photo red	640 - 670	63.900

viZaar industrial imaging AG
Hechinger Straße 152
72461 Albstadt / Germany
Tel.: +49 7432 98375-0
Fax: +49 7432 98375-50
Freecall 0800 3600371
info@vizaar.com