

MULTILED LT

MULTILED LT	
Luminous Flux	White, 14.000 lumen
Power consumption	130W
Supply Voltage	24 Vdc
Bundled PS	Standard desktop PS 24 V 150 W
Connector	XLR 4 Pin
Heat Dissipation	Heat sink with temperature controlled fan
Environmental temp. (operation)	-25°C to +40°C
Temp. (Storage)	-25°C to +80°C
Overheat Protection	Thermo switch turns off power at 72°C and turns on when temperature falls < 60°C
IP class	IP 20
Mounting Options	1/4" thread
Standard Lenses	12° FWHM
Optional Lenses	25° x 25°, 40° x 40°, 60° x 60°, 30° x 13°, 60° x 12° (horizontal x vertical)
Alternative lenses	12° Spot, medium, wide, extra wide, 120°
Dimensions	146 x 106 x 88 mm
Weight	1.365 g
LED	24 high power LED

ALTERNATIVE LED TYPES (STANDARD: COLD WHITE 14.000 LM)			
COLOR	**PEAK WAVELENGHT NM**	**LUMINOUS FL UX LM**	**RADIANT FLUX MW**
95 CRI White	Warm white	11.000	-
Light blue	460 - 480	-	49.200
Green	520 - 540	-	18.500
Red	615 - 630	-	22.000
Far red	710 - 750	-	33.000
NiR 810 nm	~ 810	-	48.500
NiR 850 nm	~ 850	-	54.800
NiR 940 nm	~ 940	-	49.300

viZaar industrial imaging AG
Hechinger Straße 152
72461 Albstadt / Germany
Tel.: +49 7432 98375-0
Fax: +49 7432 98375-50
Freecall 0800 3600371
info@vizaar.com